



Intelligent Control

- Three charging stage to protect your battery.
- RS485 communicational portal, for phone app remote control.

High efficiency

MPPT efficiency more than 99%

Battery Type

- Sealed Lead Acid battery (SLA)
- Absorbent Glass Mat Battery (AGM)
- Water battery
- Lithium battery (Li-ion)

Model	AP-20	AP-30	AP-40	AP-50	AP-60	AP-80	AP-100	AP-120
Rated Current	20A	30A	40A	50A	60A	80A	100A	120A
Maximum Charging Current	22A	32A	42A	52A	62A	82A	102A	122A

Mppt Range Operating Voltage

12VDC	18VDC~80VDC				
24VDC	30VDC~100VDC				
36VDC	40VDC~100VDC				
48VDC	60VDC~150VDC				
96VDC	Not Available	120VDC~200VDC			

Maximum Pv Array Power

12VDC	280W	420W	570W	700W	900W	1140W	1400W	1800W
24VDC	550W	840W	1130W	1400W	1700W	2260W	2800W	3400W
36VDC	840W	1260W	1710W	2100W	2700W	3420W	4200W	5400W
48VDC	1100W	1650W	2270W	2800W	3400W	4540W	5600W	6800W
96VDC	Not Available			7200W	9120W	11200W	14400W	

Battery

Supportable Battery Type	Gel/SLA/AGMWater/Lithium(lifepo4) battery				
Charging Mode	Three Stages: Constand Current(mppt), equalizing Charge, Floating Charge				
Maximum Efficiency	≥99%				

Communication Portal

Physical

Dimension, D*W*H(MM)	315*235*150	360*260*190	570*360*200
G.W.(KGS)	3.5KGS	4.5KGS	13KGS

*Product Specifications Are Subject To Change Without Further Notice